

Trace-A-Gas

A-Gas (UK) Ltd
Chemwatch: 53-0631

Chemwatch Hazard Alert Code:

Issue Date: **09/10/2015**Print Date: **17/08/2018**S.REACH.GBR.EN

Version No: **2.1.1.1**Safety Data Sheet (Conforms to Regulation (EU) No 2015/830)

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier

Product name	Trace-A-Gas
Synonyms	Not Available
Proper shipping name	COMPRESSED GAS, N.O.S. (contains nitrogen and hydrogen)
Other means of identification	Not Available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
Uses advised against	Not Applicable

1.3. Details of the supplier of the safety data sheet

Registered company name	A-Gas (UK) Ltd
Address	Banyard Road, Portbury West Bristol BS20 7XH United Kingdom
Telephone	+44 (0) 1275 376600
Fax	[+44] (0) 1275 376601
Website	www.agas.com
Email	info.uk@agas.com

1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	+44 (0) 1275 376600
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] [1]	H280 - Gas under Pressure (Compressed gas)	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

2.2. Label elements

Hazard pictogram(s)



SIGNAL WORD WARNING

Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

Supplementary statement(s)

EUH044

Risk of explosion if heated under confinement.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

P410+P403

Protect from sunlight. Store in a well-ventilated place.

Precautionary statement(s) Disposal

Not Applicable

2.3. Other hazards

Inhalation may produce health damage*.

May produce discomfort of the respiratory system*.

Vapours potentially cause drowsiness and dizziness*.

hydrogen

Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Label should state: "Restricted to professional users.")

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.7727-37-9. 2.231-783-9 3.Not Available 4.Not Available	>90	nitrogen	Gas under Pressure (Compressed gas); H280, EUH044 ^[1]
1.1333-74-0 2.215-605-7 3.001-001-00-9 4.Not Available	1-10	hydrogen	Gas under Pressure, Flammable Gas Category 1; H280, H220 ^[2]
Legend:	Classified by Che EU IOELVs available		ation drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L *

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid m	easures
Eye Contact	 If product comes in contact with eyes remove the patient from gas source or contaminated area. Take the patient to the nearest eye wash, shower or other source of clean water. Open the eyelid(s) wide to allow the material to evaporate. Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners. The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage. Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) Transport to hospital or doctor. Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage. Ensure verbal communication and physical contact with the patient. DO NOT allow the patient to rub the eyes DO NOT allow the patient to tightly shut the eyes DO NOT introduce oil or ointment into the eye(s) without medical advice DO NOT use hot or tepid water.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 Following exposure to gas, remove the patient from the gas source or contaminated area. NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.

	► Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures.
	If the patient is not breathing spontaneously, administer rescue breathing.
	▶ If the patient does not have a pulse, administer CPR.
	If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.
	▶ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further
	instruction.
	Keep the patient warm, comfortable and at rest while awaiting medical care.
	► MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.
	 Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if
	necessary.
Ingestion	Not considered a normal route of entry.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For gas exposures:	
BASIC TREATMENT	

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

ADVANCED TREATMENT

• Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

 $BRONSTEIN,\,A.C.\,and\,CURRANCE,\,P.L.$

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

 $\textbf{SMALL FIRE:} \ \textbf{Use extinguishing agent suitable for type of surrounding fire.}$

LARGE FIRE: Cool cylinder.

DO NOT direct water at source of leak or venting safety devices as icing may occur.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

The incompatibility	None Mowil.
5.3. Advice for firefighters	
Fire Fighting	GENERAL Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus and protective gloves. Fight fire from a safe distance, with adequate cover. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 Containers may explode when heated - Ruptured cylinders may rocket Fire exposed containers may vent contents through pressure relief devices. High concentrations of gas may cause asphyxiation without warning. May decompose explosively when heated or involved in fire. Contact with gas may cause burns, severe injury and/ or frostbite. Decomposition may produce toxic fumes of: nitrogen oxides (NOx) Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. DO NOT enter confined spaces where gas may have accumulated. Increase ventilation.
Major Spills	 Clear area of all unprotected personnel and move upwind. Alert Emergency Authority and advise them of the location and nature of hazard. Wear breathing apparatus and protective gloves. Prevent by any means available, spillage from entering drains and water-courses. Remove leaking cylinders to a safe place. Fit vent pipes. Release pressure under safe, controlled conditions Burn issuing gas at vent pipes. DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	 Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines. Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended. Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. DO NOT transfer gas from one cylinder to another. 	
Fire and explosion protection	See section 5	
Other information	 Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. Such compounds should be sited and built in accordance with statutory requirements. The storage compound should be kept clear and access restricted to authorised personnel only. Cylinders stored in the open should be protected against rust and extremes of weather. 	

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Cylinder: Ensure the use of equipment rated for cylinder pressure. Ensure the use of compatible materials of construction. Valve protection cap to be in place until cylinder is secured, connected. Cylinder must be properly secured either in use or in storage.
Storage incompatibility	For nitrogen: Avoid reaction with alkalis, barium oxide, lithium, silicon, calcium, strontium, barium, ozone, titanium and beryllium. Stable when temperature protected and kept isolated as a compressed gas in cylinders equipped with pressure relief safety devices. Forms cyanides when heated with carbon in the presence of alkalis or barium oxide. It can form nitrides with lithium, silicon, calcium, strontium, and barium when at red heat. Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

EMERGENCY LIMITS				
Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
nitrogen	Nitrogen	7.96E+05 ppm	8.32E+05 ppm	8.69E+05 ppm
hydrogen	Hydrogen	65000 ppm	230000 ppm	400000 ppm
Ingredient	Original IDLH		Revised IDLH	
nitrogen	Not Available		Not Available	
hydrogen	Not Available		Not Available	

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
8.2.2. Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	▶ When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	 Protective overalls, closely fitted at neck and wrist. Eye-wash unit. Ensure availability of lifeline in confined spaces. Staff should be trained in all aspects of rescue work.

Respiratory protection

- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Colourless compressed gas with no odour.		
Physical state	Compressed Gas	Relative density (Water = 1)	Not Available
Physical state	Compressed das	Relative defisity (water = 1)	NOT AVAIIABLE
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Not Available	pH as a solution (1%)	Not Available

Vapour density (Air = 1) Not Available VOC g/L Not Applicable

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicolo	ogical effects		
Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inert gas narcosis may result following exposure and is directly related to the pressure of the inert gas in the breathing gas mixture. The best known form is produced by nitrogen and is common amongst divers breathing compressed air. Inert gases of the noble gas series, except possibly helium and neon, also cause sleep and numbness. Xenon presumably acts through the formation of inert-gas hydrates which produce disturbances in nerve endings. Inhalation of non-toxic gases may cause: • CNS effects: headache, confusion, dizziness, stupor, seizures and coma; • respiratory: shortness of breath and rapid breathing; • cardiovascular: collapse and irregular heart beats; • gastrointestinal: mucous membrane irritation, nausea and vomiting. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Nitrogen is non-toxic, but may replace oxygen in inhaled air, hence causing suffocation. As the concentration of inhaled oxygen is reduced from 21% to 14% by volume, pulse rate and volume of breathing increase.		
Ingestion	Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Not considered to be a risk because of the extreme volatility of the gas.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Main route of exposure to the gas in the workplace is by inhalation.		
	тохісіту	IRRITATION	
Trace-A-Gas	Not Available	Not Available	
	TOXICITY	IRRITATION	

Trace-A-Gas	TOXICITY Not Available	IRRITATION Not Available
nitrogen	TOXICITY Not Available	IRRITATION Not Available
hydrogen	TOXICITY Not Available	IRRITATION Not Available

Trace-A-Gas & NITROGEN & HYDROGEN	No significant acute toxicological data identified in literature search.		
Acute Toxicity	\circ	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Legend:

Aspiration Hazard

🗶 – Data available but does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Mutagenicity \(\int \)

12.1. Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Trace-A-Gas	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
nitrogen	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
hydrogen	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN				
	Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5.Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product / Packaging disposal Evaporate residue at an approved site.

	 Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase. Ensure damaged or non-returnable cylinders are gas-free before disposal.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required

	2
Marine Pollutant	NO
HAZCHEM	2TE

Land transport (ADR)

14.1. UN number	1956	
14.2. UN proper shipping name	COMPRESSED GAS, N.O.S. (contain	ins nitrogen and hydrogen)
14.3. Transport hazard class(es)	Class 2.2 Subrisk Not Applicable	
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
	Hazard identification (Kemler)	20
	Classification code	1A
14.6. Special precautions for user	Hazard Label	2.2
usei	Special provisions	274 378 655 662
	Limited quantity	120 ml

Air transport (ICAO-IATA / DGR)

14.1. UN number	1956					
14.2. UN proper shipping name	Compressed gas, n.o.s. * (contains nitrogen and hydrogen)					
14.3. Transport hazard	ICAO/IATA Class	2.2				
class(es)	ICAO / IATA Subrisk	Not Applicable				
	ERG Code	ERG Code 2L				
14.4. Packing group	Not Applicable					
14.5. Environmental hazard	Not Applicable					
	Special provisions		A202			
	Cargo Only Packing Instructions		200			
	Cargo Only Maximum Qty / Pack		150 kg			
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		200			
	Passenger and Cargo Maximum Qty / Pack		75 kg			
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden			
	Passenger and Cargo Limited Maximum Qty / Pack		Forbidden			

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1956
14.2. UN proper shipping name	COMPRESSED GAS, N.O.S. (contains nitrogen and hydrogen)
14.3. Transport hazard class(es)	IMDG Class 2.2 IMDG Subrisk Not Applicable

14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	F-C,S-V
	Special provisions	274 378
	Limited Quantities	120 mL

Inland waterways transport (ADN)

14.1. UN number	1956				
14.2. UN proper shipping name	COMPRESSED GAS, N.O.S. (contains nitrogen and hydrogen)				
14.3. Transport hazard class(es)	2.2 Not Applicable				
14.4. Packing group	Not Applicable				
14.5. Environmental hazard	Not Applicable				
	Classification code	1A			
	Special provisions	274 378; 655; 662			
14.6. Special precautions for user	Limited quantity	120 ml			
usei	Equipment required	PP			
	Fire cones number	0			
	ļ	•			

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

NITROGEN(7727-37-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex IV - Exemptions from the Obligation to Register in Accordance with Article 2(7)(a) (English)

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

HYDROGEN(1333-74-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Europe European Customs Inventory of Chemical Substances - ECICS (Slovak)

Europe European Customs Inventory of Chemical Substances ECICS (Bulgarian)

Europe European Customs Inventory of Chemical Substances ECICS (Czech)

Europe European Customs Inventory of Chemical Substances ECICS (Romanian)

European Customs Inventory of Chemical Substances ECICS (English)

 $\label{thm:commercial} \textbf{European Inventory of Existing Commercial Chemical Substances (EINECS) (English)}$

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2015/830; Regulation (EC) No 1272/2008 as updated through ATPs.

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
nitrogen	7727-37-9.	Not Available	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Press. Gas (Comp.)	GHS04; Wng	H280
2	Press. Gas (Comp.); Press. Gas (Ref. Liq.); Press. Gas (Liq.); Press. Gas (Diss.); Skin Irrit. 2; Eye Irrit. 2; Acute Tox. 4; STOT SE 3; Muta. 1B; Carc. 1A	GHS04; GHS08; Dgr	H280; H281; H315; H319; H332; H335; H340; H350
1	Skin Sens. 1; Eye Irrit. 2; Aquatic Acute 1; Aquatic Chronic 1	GHS09; GHS07; Wng	H317; H319; H410
2	Skin Sens. 1; Eye Irrit. 2; Aquatic Acute 1; Aquatic Chronic 1	GHS09; GHS07; Wng	H317; H319; H410

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
hydrogen	1333-74-0	001-001-00-9	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Gas 1; Press. Gas (Comp.)	GHS02; GHS04; Dgr	H220; H280
2	Flam. Gas 1; Press. Gas (Comp.); Press. Gas (Ref. Liq.); Ox. Gas 1; Resp. Sens. 1; Muta. 1B; Carc. 1A; Press. Gas (Liq.)	GHS02; GHS04; Dgr; GHS03; GHS08	H220; H280; H281; H270; H334; H340; H350

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory Status

National Inventory	Status	
Australia - AICS	ү	
Canada - DSL	Υ	
Canada - NDSL	N (hydrogen; nitrogen)	
China - IECSC	Υ	
Europe - EINEC / ELINCS / NLP	Y	
Japan - ENCS	N (hydrogen; nitrogen)	
Korea - KECI	Y	
New Zealand - NZIoC	Υ	
Philippines - PICCS	N (nitrogen)	
USA - TSCA	Υ	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Revision Date	09/10/2015
nevision bute	03/10/2013
Initial Date	Not Available

Full text Risk and Hazard codes

H220	Extremely flammable gas.	
H270	May cause or intensify fire; oxidiser.	
H281	Contains refrigerated gas; may cause cryogenic burns or injury.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H340	May cause genetic defects.	
Н350	May cause cancer.	
H410	Very toxic to aquatic life with long lasting effects.	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average

 ${\tt PC-STEL: Permissible Concentration-Short Term\ Exposure\ Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.